

SECTION 1. PRODUCT IDENTIFICATION

Product identifier used on label

SkidGuard Primer

Material Uses Primer coat for metal, concrete or wood, in order to improve adhesion of top coat sealer
Product Type Liquid until dry, then solid
Chemical name Hydrocarbon Emulsion
Product Class Polymer Modified Asphalt Emulsion

Recommended use and restrictions:

Identified uses SKIDGUARD PRIMER is primer coat, designed to be applied prior to other Carbonyte coatings to improve adhesion between coating and surfaces such as on steel road plates, man-hole & vault covers, ramps, walkways, roadways.
Uses advised against Not applicable
Reason Not applicable

Supplier/Manufacturer Carbonyte Systems, Inc.
 3 Wayne Court Suite A, Sacramento, CA 95829
 Phone: 916-387-0316 Fax: 916-388-1359 www.carbonyte.com

Emergency Information CHEMTREC 800-424-9300

SECTION 2. HAZARDOUS IDENTIFICATION

CAS# Mixture

WARNING



Health 1
 Flammability 0
 Reactivity 0
 Personal Protection Equipment A

Hazard Statement: Possible Irritant to skin, mucous membranes, airways, lungs, eyes, stomach. Target organs – upper respiratory tract.

Classification: RESPIRATORY SENSITIZER: Category 1B – see “INHALATION” below

Health Risks & Symptoms of Exposure:

SKIN & EYE: Irritant to eyes and to the skin of some individuals. Wash skin with plenty of water; if splashed in the eye, flush with water for 15 minutes.

INGESTION: Ingestion of this material is not expected to occur through normal use. Accidental ingestion of more than one ounce may cause irritation. Contact a physician should ingestion occur.

INHALATION: Irritant to mucous membranes. Dust from cured coating may provoke asthmatic response in persons with asthma or those who are sensitive to airway irritants.

ACUTE & CHRONIC Health Hazards: Product may contain trace amounts of vinyl acetate which has been shown to cause tumors of the respiratory tract of laboratory animals. There is no evidence that it has caused cancer in humans.

Target Organs Affected: Upper respiratory tract.

Substances Listed in State of California Proposition 65: Petroleum asphalt may contain trace amounts of benzene (CAS #71432). Contains trace amounts of residual acrylate an styrene monomers and <0.1% residual acrylamide monomer and formaldehyde. Contains ammonia <0.1% max.

SECTION 3: Composition/Ingredient Information

INGREDIENTS *	CAS NUMBER	% By Weight
<i>Petroleum Asphalt</i>	8052-42-4	<70
<i>Co-Polymer Latex</i>	Proprietary	<10
<i>Synthetic Rubber</i>	Proprietary	<20
<i>Surfactant</i>	Proprietary	<2

* The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a Trade Secret.

SECTION 4: First Aid Measures

Inhalation If inhalation of vapors causes a perceived irritation of respiratory tract, remove victim to fresh air and seek medical advice

Skin Contact In the event of skin contact, wash skin with water and soap.

Eye Contact If splashed in eye, flush 15 minutes in eyewash and seek medical advice.

Swallowed If swallowed into stomach, DO NOT induce vomiting or aspiration. Call a physician

Most important symptoms and effects, both acute and delayed, see SECTION 2.

Indication of any immediate medical attention and special treatments required NOT APPLICABLE.

SECTION 5: Fire-Fighting Measures

Flammability Classification: OSHA: Not Regulated

Flash Point: None

Extinguishing Media: Dry Chemical & CO₂; for dry polymer

Unusual Fire & Explosion Hazards: None

Special Fire Fighting Procedures: Dried polymer burns under influence of outside flame source but will self -extinguish at temperatures below ~80°F. By-products of combustion may include, carbon monoxide, traces of oxides of nitrogen, aliphatic and aromatic hydrocarbons, hydrogen bromide, water, and traces of styrene acrylic monomer. By -products of pyrolysis may include acetic acid, acrolein, and acetaldehyde. Wear positive pressure, self -contained breathing apparatus (SCBA) during fire or cleanup.

SECTION 6: Accidental Release Measures

Absorb spill with appropriate absorbent material such as sand, sawdust, clays, etc. Dike and contain spills; transfer liquid to containers for recovery or disposal. Do not dump in sewers, on ground, or into any body of water.

SECTION 7: Handling and Storage

This product is stable under normal use and storage conditions. Keep out of reach of children. Recommend storage at temperatures above 32°F - 100°F (0 - 38°C). Use with adequate ventilation.

SECTION 8: Exposure Control/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV TWA STEL	OSHA PEL
	<i>Petroleum Asphalt</i>	None	5 mg/m
	<i>Co-Polymer Latex</i>	None established	N/A
	<i>Synthetic Rubber</i>	None	N/A
	<i>Surfactant</i>	None	N/A

Respiratory Protection: Not required for outdoor application. If odors become noticeable or respiratory irritation occurs during application use NIOSH/MSHA approved respirator for organic vapors, at employee discretion.

Ventilation: Ensure adequate supply of fresh air at all times. If buildup of vapor causes irritation, use mechanical ventilation sufficient to eliminate the vapor which causes the irritation.

Protective Gloves: Nitrile rubber (Buna N) if required to prevent repeated or prolonged skin contact.

Eye Protection: Wear chemical goggles at all times when handling this product.

Other Protective Wear approved respirator, gloves, hat, shoes, and long-sleeved clothing to prevent

Clothing or Equipment: contact with the material.

SECTION 9: Physical & Chemical Properties

Ingredient Name	Vapor Pressure	Boiling Point:	~100°C	Density:	8.0 - 10.0 lbs./gal
Petroleum Asphalt	<1mm Hg@20 C of water	Evaporation Rate:	Of water	pH:	7 - 10
Co-Polymer Latex	n/a	Solubility in Water:	Miscible	SP. GR.	0.9 - 1.3
Synthetic Rubber	n/a	% Volatile by Volume:	12-50%	V.O.C.:	<10 grams / litre
Inorganic Fillers	n/a	Vapor Density:	Heavier than air		
		Appearance/Odor:	Various colors, flowable liquid, pleasant sweet odor		

SECTION 10: Stability & Reactivity

Stability:	<input checked="" type="checkbox"/> Stable	<input type="checkbox"/> Unstable
Hazardous Polymerization:	<input checked="" type="checkbox"/> Will Not Occur	<input type="checkbox"/> May Occur
Hazardous Decomposition Products:	None Known	
Incompatibility:	Product will react violently with any water sensitive material such as sulfuric acid or alkali materials such as sodium or metal hydrides. May react with strong oxidizing agents such as hydrogen peroxide or permanganates resulting in intense heat, boiling, flame development, explosion or toxic gas generation.	
Conditions to Avoid:	Do not store at temperatures below 32°F – or above 100°F (0 - 38°C)	

SECTION 11: Toxicological Information

Carcinogenicity:	NTP? NO
IARC	MONOGRAPHS? NO
OSHA	REG.? NO

SECTION 12: Ecological Information

Do not dump in sewers, on ground, or into any body of water.

SECTION 13: Disposal Considerations

Waste Disposal Method: Dispose of in accordance with prescribed federal, state, and local regulations.

SECTION 14: Transport Information

DOT: Not Regulated

SECTION 15: Regulatory Information

U.S. Federal Regulations 311/312 Hazard Categories:

Fire Hazard:	NO	Reactivity Hazard:	NO	Delayed Hazard:	NO
Pressure Hazard:	NO	Immediate Hazard:	NO		

TSCA: Ingredients in this product are certified for inclusion in the Toxic Substances Control Act of inventory of chemical substances.

OSHA: Product contains material as defined by 29CFR Paragraph 1910, 1200. Components of product are not listed by the National Toxicology Program, the International Agency for Research on Cancer, nor the Registry of Toxic Effects of Chemical Substances (1981-82) as a carcinogen.

SARA Title III: Product contains the following listed toxic chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and 40 CFR, Part 372.

<u>Listed Toxic Chemical</u>	<u>CAS #</u>	<u>Max % by Wt.</u>
None	N/A	N/A

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other Information**NFPA Hazard Classification**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 1 **Flammability:** 0 **Physical Hazard:** 0 **Personal Protection:** None

Hazardous Material Identification System (HMIS[®]III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS[®]III ratings are to be used with a fully implemented HMIS[®]III program. HMIS[®] is a registered mark of the American Coatings Association (ACA).

Issue Date: 11/30/2015

Supersedes Date: 01/31/2012

Version Number: 1.0

DISCLAIMER: The information in this Safety Data sheet (SDS) is believed to be correct as of the date issued. CARBONYTE SYSTEMS, INC. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Carbonyte Systems, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a CARBONYTE SYSTEMS, INC. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate this product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

CARBONYTE SYSTEMS, INC. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, CARBONYTE SYSTEMS, INC. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from CARBONYTE SYSTEMS, INC.

For technical information regarding performance of this product, call CARBONYTE SYSTEMS, INC. at (916) 387-0316 or fax (916) 388-1359 or email at sales@carbonyte.com SDSs are available at www.Carbonyte.com